



RAYXSCAN

X-Ray Gauging System

The **RAYXSCAN** uses an X ray beam transmission through the homogeneous material to be measured, from which it can measure the thickness, usually shown in micron or the weight [g/m²].

PRINCIPLE OF OPERATION

An X-ray source is situated in a housing, while another housing contains the receiver and is positioned opposite the transmitter at a set distance (Gap). When a homogeneous layer of material is positioned between the transmitter and receiver, part of the energy transmitting to the receiver is absorbed by the material. The part which is not captured by the receiver is directly proportional to the thickness of the measured film according to the main features of the material.



MAIN FEATURES

NON RADIOACTIVE

Following the regulations EURATOM 96/29, RAYXSCAN is not considered a radioactive source because the tension on the anode is lower than 5 kV, for this reason this scanner does not need to follow the radio protection regulations and hence a safety certificate is not necessary.

INDUSTRY 4.0 & IoT

RAYXSCAN is equipped with PLC integrated with OPC-UA protocol for industry 4.0.

SYNTROL CONTROL

RAYXSCAN is equipped with Control cabinet along with PC touch screen, keyboard, mouse and printer.

PROCESSES

RAYXSCAN can be used on different process such as stretch film lines, non-woven lines, BOPP lines, coating lines, Blown film lines.

LIMITLESS PERFORMANCES

The measurement is not influenced by color, transparency or by material composition.

HEAVY DUTY STRUCTURE

The heavy duty engineering offers excellent resistance to bending of the main frame and guarantees perfect measurement stability.

EASY ACCESS FOR MAINTENANCE

The RAYXSCAN has been designed to guarantee easy access for maintenance operations.

FAST SET UP

The average startup is done in less than 2h.


STABLE AND PRECISE

Extremely stable and precise measurement: down to 0.02 micron of repeatability with a max. drift without standardization in 12 h of 0.085 microns. True air gap density compensation with pressure and temperature measurement.

AUTO PROFILE CONTROL

As option RAYXSCAN can be connected to SYNTROLGAUGE to control automatically the thermal bolts used on flat dies or automatic air ring on blow film lines to regulate the film/sheet profile.

TECHNICAL DATA



Model	W max Film width	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	f (mm)	g (mm)	Power (kW/h)	Weight (kg)
1000	1000	2385	350	1020	920	465	200	810	0.8	286
1200	1200	2585								293
1400	1400	2785								308
1600	1600	3085				323				
1800	1800	3285				336				
2000	2000	3485				350				
2200	2200	3835		363	1100	1020	210	830		376
2400	2400	4035		390						
2600	2600	4235		403						
2800	2800	4435		416						
3000	3000	4635		430						
3200	3200	4835		470						
3600	3600	5235		520	1070					560
4000	4000	5685		600						
4400	4400	6085								
4800	4800	6485								